



# QuarryTile 1500™DTQ Primer

SDS SAFETY DATA SHEET

DTQ 1500™ by InduraFloor - THE SOLUTION FOR QUARRY TILE

Part 1: IDENTIFICATION

Date Prepared or Revised: April 4, 2023. Rev. August 01, 2023, for physical property (color).

For most current SDS go to www.InduraFloors.com

Product Name: QuarryTile 1500™ DTQ Primer

Recommended use: Two-component coating to be applied directly over Quarry Tile and grout

Chemical Classification: Modified epoxy with additives

Manufacturer: InduraFloor, Inc.

7251 Garden Grove Blvd. Suite K Garden Grove, CA 92841 USA

Emergency Contact: Contact your local emergency services or

Contact Chemtrec (24-hr): 1-800-424-9300

## Part 2: HAZARDS IDENTIFICATION

## **Label Elements GHS-US**

## Hazard Pictograms:









Signal Word: Danger

Statements:

## Hazard Statements (GHS-US)

H226 Flammable liquid and vapor
 H315 Can Cause skin irritation.
 H319 Can Cause serious eye irritation.
 H317 May cause allergic skin reaction.
 H351 Suspected of causing cancer.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary Statements** 

P202 Do not handle until all safety precautions have been read and understood

P102 Keep out of reach of children

P264 Wash hands thoroughly after handling P273 Avoid release to the environment

## **Responsive Precautionary Statements**

P264 Wash thoroughly after handling

P280 Wear protective gloves / protective clothing / eye protection / face protection.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P301 + +P330 + P331 + P310 IF SWALLOWED: Rinse mouth, do not induce vomiting. Immediately call a POISON CENTER or

doctor / physician.



## Part 3: COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS No.	Percent (%)
Modified Bisphenol A epoxy	Closed	Closed
Proprietary trade secret	Closed	Closed
Titanium dioxide	13463-67-7	1 - 2%
Acetone	67-64-1	20 - 30%

#### Part 4: FIRST AID MEASURES

When seeking medical advice take this safety data sheet with you.

#### Eye Contact:

Immediately flush eyes cautiously with plenty of water. Remove contact lenses. Continue to rinse for at least 20 minutes. Do not rub eyes as this may cause irritation or cause damage. If irritation persists, seek immediate professional medical attention.

#### Skin Contact

Quickly and gently wash with plenty of soap and water. Remove contaminated clothes and shoes. Continuously flush the contaminated area with lukewarm gently flowing water for at least 20 minutes. If skin irritation or rash occurs, seek medical advice / attention.

#### Inhalation:

Remove victim to fresh air and keep at rest in a comfortable position. If not breathing, or if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Seek medical attention. If unconscious, place in recovery position and maintain an open airway. Get medical attention immediately.

#### Ingestion:

Wash out mouth with water. Move victim to fresh air and in a comfortable rest position. If the victim is conscious, give small amounts of water to drink. Stop if the victim feels sick as vomiting may be dangerous. Do not induce vomiting. If vomiting occurs, head should be kept low so that the vomit does not enter the lungs. Get medical attention. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Contact poison control center.

## Most Important Symptoms and effects, both acute and delayed:

#### Acute Health Effects:

Eye Contact: Causes serious eye irritation.

Inhalation: No known significant effects or critical hazards.

Skin Contact: Causes skin irritation.

Ingestion: No known significant effects or critical hazards.

#### Delayed Health Effects:

Eye Contact: Adverse symptoms may include pain or irritation, watering and redness.

Inhalation:No known significant effects or critical hazards.Skin Contact:Adverse symptoms may include irritation and redness.Ingestion:No known significant effects or critical hazards.

## Part 5: FIRE FIGHTING MEASURES

Flammability: Flammable liquid Class 1B

Flash Point: 192°F Upper Explosive Limit: 27% Lower Explosive Limit: 3%

Suitable Extinguishing Media: CO2, foam, dry chemical and water

Fire Fighting Measures: Cool containers with water to prevent pressure build-up. Wear full protective equipment

and NIOSH full-contained breathing apparatus

Specific Hazards: Toxic to aquatic life. Fire water must be contained and prevented from discharge into waterways, sewers

or drains



#### Part 6: ACCIDENTAL RELEASE MEASURES

Spill & Leak Measures: Stop leak if possible without risk to self or others. Move containers from spill area. Contain and collect spillage with

non-combustible absorbent material (sand, earth, vermiculite, diatomaceous earth) and place in container for disposal

in accordance with regulations, both Federal and local.

Specific Hazards: Toxic to aquatic life. Spill must be contained and prevented from discharge into waterways, sewers or drains.

#### Part 7: HANDLING AND STORAGE

Do not eat, drink or smoke when handling or applying product. Remove contaminated clothing and protective equipment before entering eating areas.

Store locked up and out of reach of children. Do not store in direct sunlight. Do not expose to freezing temperatures. Store in upright position. Store in accordance with local regulations. Store in original containers in a dry, cool and well-ventilated area between 60°F and 80°F. Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright.

#### Part 8: PERSONAL PROTECTION

#### **Exposure Limits:**

Exposure LimitLimitFor time weighted avg.Modified Bisphenol-A epoxy:nonenonenoneTitanium dioxide:ACGIH TLV TWA10 mg/m38 hrs.Acetone:TWA PEL750 ppm8 hrs.

Appropriate Engineering Controls: If operations generate dust, fumes or gas, use ventilation.

## **Individual Protective Measures:**

Hygiene Measures: Wash hands and forearms after use.

Protective Measures:

Eye/face Protection Wear protective eyewear for splashes of product.

Hand Protection Wear chemical resistant gloves.

Body Protection Wear appropriate protective clothing based upon the tasks to be performed.

Feet Protection Wear non-slip and chemical resistant footwear.

Respiratory Protection Based upon the circumstances and need, select a respirator that meets the appropriate standards.

## Part 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State Viscous liquid

Color translucent to light grey when mixed

Odor Mild, epoxy
VOC None
Density 1.2

Boiling Point 133°F - 350°F

#### Part 10: STABILITY AND REACTIVITY


Reactivity and Chemical Stability: Stable under normal conditions.

Conditions to Avoid: No specific data.

Hazardous Decomposition: None under normal storage and use. When there is a fire, decomposition products may include carbon

dioxide, carbon monoxide, halogenated compounds, metal oxides.

Incompatible Materials: Oxidizing materials.





## Part 11: TOXICOLOGICAL INFORMATION

#### Potential Acute Health Effects:

Eye Contact: Causes serious eye irritation. Inhalation: No known significant hazards.

Skin Contact: Cause skin irritation.

Ingestion: No known significant hazards.

Symptoms:

Eye Contact: Pain, irritation, watering, redness. Inhalation: No known significant hazards.

Skin Contact: Irritation, redness.

Ingestion: No known significant hazards.

Chronic Effects:

Short Term Exposure: No known significant hazards. Long Term Exposure: No known significant hazards.

Chronic Effects: Carcinogenicity: Suspected of causing cancer.

Mutagenicity: No known significant hazards.
Teratogenicity: No known significant hazards.
Developmental effects: No known significant hazards.
Fertility effects: No known significant hazards.

Specific Organ Toxicity:

For repeated exposure: No data available. Aspiration Hazard: No data available.

## Part 12: ECOLOGICAL INFORMATION

Ecotoxicity: Do not allow the material to enter water course. If water is contaminated inform the relevant authorities immediately. This product may be toxic to aquatic life under certain circumstances.

Toxicity: Acetone: LD50 Dermal >9400 uL/kg (guinea pig); LD50 Oral 5800 mg/kg (rat).

Titanium dioxide, Acute LC50>1,000,000 ug/L, marine water, 96 hrs.

Persistence and Degradability: No data available. Mobility in Soil: No data available.


## Part 13: DISPOSAL CONSIDERATIONS

Disposal Method: Dispose in accordance with current Federal, State, Local and/or international laws and regulations.

# Part 14: TRANSPORTATION INFORMATION

DOT: Paint related material 3.
Hazard Class: Class 3, PG II, limited quantity.

UN Number: UN 1263.





Part 15: REGULATORY INFORMATION

U.S. Federal: All components are listed or exempted on TSCA 8b.

SARA 311/312: SKIN CORROSION/IRRITATION Category 2

SERIOUS EYE DAMAGE/IRRITATION Category 2A
SKIN SENSITIZATION Category 1
CARCINOGENICITY Category 2

USA Hazardous Materials Info: HEALTH 2

FLAMMABILITY 1B PHYSICAL HAZARDS 0

#### Part 16: OTHER INFORMATION

#### Abbreviations:

GHS Globally Harmonized System of Classification and Labeling of Chemicals

CAS Chemical Abstract Service Number

TWA PEL time-weighted average (TWA) permissible exposure limit (PEL)

NIOSH National Institute for Occupational Safety and Health SARA Superfund Amendments and Reauthorization Act

## Disclaimer:

InduraFloor believes the information contained herein is accurate; however, InduraFloor makes no guarantees with respect to such accuracy and assumes no liability in connection with the use of the information contained herein which is not intended to be and should not be construed as legal advice or as insuring compliance with any federal, state, provincial or local laws or regulations. Any party using these products should review all such laws, rules, regulations prior to use.

The information in this SDS is generated for the purpose of distributing known health, safety and environmental information and is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user. Information was obtained from sources that we believe are accurate and reliable. The conditions or methods of handling, storage, use or disposal are beyond our control. For this and any other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the material.